


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)

object pointer key

Search

[Advanced Search](#)
[Preferences](#)

Web

Results 21 - 30 of about 2,570,000 for object pointer key. (0.11 seconds)

Object Computing, Inc. - CORBA News Brief - November 2002

This article focuses on **object** references, the basic **pointer** (`_ptr`) type, ...

This operation receives a Hello **object** reference along with its **key**, ...

www.ociweb.com/cnb/CORBANewsBrief-200211.html - 34k - [Cached](#) - [Similar pages](#)

Berkeley DB: Dbt

Both **key** and data items are represented by Dbt **objects**. ... Given a const Dbt

object, Dbt::get_const_DBT returns a const **pointer** to the same struct. ...

www.sleepycat.com/docs/api_cxx/dbt_class.html - 14k - [Cached](#) - [Similar pages](#)

Setting Security on an Asynchronous Call [WMI]

... of registry **key** wszReserved, &pStubSink);. Release the sink **object pointer**.

You can release the **object pointer** because the stub now owns the **pointer**. ...

msdn.microsoft.com/library/en-us/wmisdk/wmi/setting_security_on_an_asynchronous_call.asp - 21k - [Cached](#) - [Similar pages](#)

XML-Security-C: XSECCryptoProvider Class Reference

Call used by the library to obtain a DSA **key object**. Returns:: **Pointer** to the

new DSA **key**. See also:: XSECCryptoKeyDSA. Implemented in OpenSSLCryptoProvider ...

xml.apache.org/security/c/apiDocs/classXSECCryptoProvider.html - 36k - [Cached](#) - [Similar pages](#)

Boost Pointer Container Library

The problem refers to the relatively troublesome way C++ supports **Object Oriented**

... in connection with containers of **pointers** to polymorphic **objects**. ...

www.boost.org/libs/ptr_container/doc/faq.html - 12k - [Cached](#) - [Similar pages](#)

[[More results from www.boost.org](#)]

Qt 4.0: QCache Class Reference

Returns a **pointer** to the **object** taken out, or 0 if the **key** does not exist in the cache. The ownership of the returned **object** is passed to the caller. ...

doc.trolltech.com/4.0/qcache.html - 13k - [Cached](#) - [Similar pages](#)

Contents

|Where You Can Specify an **Object** Field · Basing **Pointer** Data Type ... User Controlled

Support for Null-Capable Fields and **Key** Fields · Input-Only Support ...

publib.boulder.ibm.com/series/v5r1/ic2924/books/c092508302.htm - 69k - [Cached](#) - [Similar pages](#)

ILE C/C++ Programmer's Guide - Contents

Example: Passing OS/400 **pointers** as Arguments on a Dynamic Program Call to Another

ILE C Program ... Passing a `_DecimalT` Class Template **Object** to a Function ...

publib.boulder.ibm.com/infocenter/iadthelp/topic/com.ibm.etools.iseries.pgmgd.doc/cpprog02.htm - 67k -

[Cached](#) - [Similar pages](#)

[[More results from publib.boulder.ibm.com](#)]

PDF nag_search_vector (m01fsc)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Boolean nag_search_vector(**Pointer** key, **Pointer** vec, size_t n, ... Parameters.

key. Input: the **object** to search for. vec[]. Input: the array of **objects** to ...

www.nag.co.uk/numeric/cl/mk6manual/pdf/M01/m01fsc_cl05.pdf - [Similar pages](#)

[doc] (private and confidential)

File Format: Microsoft Word 2000 - [View as HTML](#)

Mus be able to send back the **Key** that can give access to an **object** in a specific
... a DRM Provider Broker System **Key** to an **object** or **object pointer**. ...

www.edusource.ca/documents/ed-dev/drmA03requirements2003m05d25final.doc - [Similar pages](#)



Result Page: [Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [Next](#)

object pointer key

Search

[Search within results](#) | [Language Tools](#) | [Search Tips](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Hurricane Katrina Resources](#) - [About Google](#)

©2005 Google